

## HAR44EL



FALL ARRESTER HARNESS WITH BELT - 4 ANCHORAGE POINTS - DIELECTRIC Ref. HAR44EL



#### Product specifications

Dielectric harness with positioning belt. 2 fall arrester anchorage points (back - front). 4 adjustable buckles. Positioning belt with thermoformed back closed with wide Velcro for more comfort. 180° rotation. 2 lateral anchorage points for work positioning. Sponge back lining. Buckles with plastic coating. Material insulates to 20kV.

Straps: Polyester.

Buckles: 100% plastic coating.

COLOUR Black-Grey

SIZE

S/M/L, XL/XXL

















Vertical movement on a permanent structure








Short vertical movement or movement on inclined surface (less than 3 m)















→ Long horizontal movement on vertical structure Short horizontal



### Product's highlights & user's benefits

**DIELECTRIC** 

Insulator up to 30KV



2 accessory attachment holders incorporated

Anchorage carabiners, lanyards and tools



180° rotation

Easy rotation of the basin



#### Certifications and Standards

# **(**E

#### **REGULATION (EU) 2016/425**

EN363: 2008 Personal fall protection equipment - Personal fall protection systems

EN364: 1992 Personal protective equipment against falls from a height: Test method

EN365 : 2004 Personal protective equipment against falls from a height – General requirements for the instructions for use, maintenance, periodic examination, repair, marking and packaging.

EN361 : 2002 Personal protection equipment against falls from a height - Full body harnesses 100 kg: Additional special requirements

EN358: 2018 Personal protective equipment for work positioning and prevention of falls from a height – Belts and lanyards for work positioning or restraint.

References					
References	Bar code	COLOUR	SIZE		À
HAR44ELGT	3295249203504	Black-Grey	S/M/L	5	-
HAR44ELXX	3295249204723	Black-Grey	XL/XXL	5	-