

EOS NOCUT VV910



HIGH PERFORMANCE POLYETHYLENE KNITTED GLOVE - DOUBLE NITRILE-COATING PALM

Ref. VV910



Product specifications

High performance polyethylene support. Thermoplastic (TPR) reinforcement on back and fingertips. Smooth nitrile coating/foam nitrile on palm and fingertips. Embossed inside reinforcement on palm. Kevlar® thread on all the seams.

Support: High performance polyethylene fibre.

Coating: nitrile.

Back reinforcement: TPR.

COLOUR

Yellow-Grey-Black

SIZE

08, 09, 10, 11

Product Use - Risks



CUTTING



Wearing



Shock



PERFORATION



Second work / craftman



Services / Logistics



Construction / Civil engineering



Heavy industry



Oil / Gas

Product's highlights & user's benefits



Double nitrile coating for oily work

1st smooth nitrile coating : impermeable to oils
2nd nitrile foam coating : good adhesion



Flexible reinforcements

Increased protection from impacts and pinches



Reinforcement between the thumb and index finger and on the palm

Increased protection



Protection against impact in the metacarpal area. After an energy impact of 5J, the force transmitted to the back of the hand cannot exceed 4 kN



Available only with header card

Very good abrasion and cut resistance

Increased lifespan

Kevlar® thread stitching

Increased lifespan

8 cm cuff with Velcro closure

Perfect adjustment
Reduced discomfort at the wrist, during prolonged use

Safe, qualitative and very comfortable; the EOS NOCUT is surely one of the gloves with the most interest on the market!



Cut level D

Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements
5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

4: Resistance to abrasion (from 1 to 4)

X: Resistance to cutting (from 1 to 5)

4: Resistance to tear (from 1 to 4)

3: Resistance to puncture (1 to 4)

D: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

P: Protection against impact in metacarpal area (P) (EN13594:2002 6.8.2)



EN13594:2002 4.1.3/6.8.2. Impact energy attenuation



USA STANDARDS



ANSI-ISEA 105:2016 Hand protection

A4: Resistance to cutting by sharp objects (from A1 to A9)

References

References	Bar code	COLOUR	SIZE		
VV910JA08	3295249191542	Yellow-Grey-Black	08	60	12
VV910JA09	3295249191559	Yellow-Grey-Black	09	60	12
VV910JA10	3295249191566	Yellow-Grey-Black	10	60	12
VV910JA11	3295249191573	Yellow-Grey-Black	11	60	12