

XR502 S3 SRC



NYLON MESH/NUBUCK LEATHER SHOES - S3 HRO SRC

Ref. XR502S3



Product specifications

Upper: Nubuck leather and nylon mesh, S3 water resistant treatment. Lining: Polyamide absorbing. Insock: Removable preformed - Polyamide on EVA. Midsole: Cemented - PU with shock absorber Panoshock®. Outsole: Rubber. Non metallic shoe.

COLOUR

Black

SIZE

39, 40, 41, 42, 43, 44, 45, 46, 47

Product Use - Risks



Antistatic



Slip



Heat



Shock



Second work / craftman



Light industry



Services / Logistics

Product's highlights & user's benefits



PU/RUBBER CEMENTED OUTSOLE

- 1- Flex-Zone
- 2- Antislip rubber
- 3- TPU foot arch reinforcement



Speed lace



Composite toe cap 200- joule,
Lighter than steel
Non conductive material



NON-METALLIC



Ultra flexible anti-perforation composite
insole



PANOSHOCK® system
For reduced fatigue & added comfort

DELTA INNOVATION



COMPOSITE

Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 20344:2011 Personal protective equipment - Test methods for footwear

EN ISO 20345:2011 Personal protective equipment - Safety footwear.
S3 HRO: Additional special requirements
SRC: Slip resistance

USA STANDARDS



ASTM F 2413:2011 Standard Specification for Performance Requirements for Protective (Safety) Toe Cap Footwear.
M I/75 C/75 PR SD: Additional special requirements

References

References	Bar code	COLOUR	SIZE		
XR502S3NO39	3295249195137	Black	39	5	-
XR502S3NO40	3295249195212	Black	40	5	-
XR502S3NO41	3295249195229	Black	41	5	-
XR502S3NO42	3295249195250	Black	42	5	-
XR502S3NO43	3295249195267	Black	43	5	-
XR502S3NO44	3295249195274	Black	44	5	-
XR502S3NO45	3295249195298	Black	45	5	-
XR502S3NO46	3295249195311	Black	46	5	-
XR502S3NO47	3295249195328	Black	47	5	-